MATERIAL SAFETY DATA SHEET

HARRY J. BOSWORTH COMPANY

7227 North Hamlin Avenue Skokie, Illinois 60076-3999

Information Phone: 847.679.3400 Emergency Phone: 800.535.5053 HAZARD RATING

4 - EXTREME

F 3 - HIGH

P 2 - MODERATE

A 1 - SLIGHT 0 - INSIGNIFICANT Health 1 10 Reactivity

PRODUCT:

Supergel® Fresh Alginate Regular and Fast Set

DATE PREPARED: 11/01/0

Hazardous Components		
INGREDIENTS: 1. Potassium Fluotitanate 2. Diatomaceous Earth	PERCENTAGE: 1. N/A 2. N/A	
COMMON NAMES AND SYNONYMS: 1. Inorganic Fluoride Salt 2. Silica	CAS NUMBER: 1. 16919-27-0 2. 14464-46-1	
PEL: 1. 2.5 mg/m ³ Flouride 2. 0.05 mg/m ³ Silica, respirable	UN NUMBER: 1. UN 1760 2. N/A	
TLV: 1. 2.5 mg/m ³ Flouride 2. 0.05 mg/m ³ Sllica		

Physical/Chemical Characteristics		
BOILING POINT/FLASH POINT: N/A	pH: N/A	
VISCOSITY: N/A	DENSITY: g/cm³ N/A	
VAPOR PRESSURE: N/A	EVAPORATION RATE: (Butyl Acetate = 1) N/A	
APPEARANCE/ODOR: Off white fine powder. Distinct odor of sassafras with menthol	SOLUBILITY IN WATER: Forms gel	

Reactivity Data	Fire and Explosion Hazard Data		
STABILITY: Stable	FLASH POINT: LIMI N/A LEL: UEL	N/A	
CONDITIONS TO AVOID: Avoid heat over 25°C (77°F) and humidity over 50%.	EXTINGUISHING MEDIA: Water, foam, dry chemical and CO₂		
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, fluoride, suiphur and potassium compounds	SPECIAL FIREFIGHTING PROCEDURES: Use proper protective clothing. Fight fire from safe distance		
HAZARDOUS POLYMERIZATION: Will not occur	UNUSUAL FIRE AND EXPLOSION HAZARDS: No unusual fire or explosion hazards are associated with this material.		
CONDITIONS TO AVOID: Avoid oxidizing agent, strong acid and excessive heat over 140°			

CARCINOGENICITY: California Proposition 65 Warning: This product may contain a chemical known to the state of California to cause cancer IARC: N/A OSHA REGULATED: N/A

Effects and Hazards of Overexposure (Acute and Chronic)

EFFECTS AND HAZARDS OF EYE CONTACT: May cause irritation upon prolonged exposure.

EFFECTS AND HAZARDS OF SKIN CONTACT: None except drying of skin

EFFECTS AND HAZARDS OF INHALATION (BREATHING): Prolonged exposure to excessive concentration of dust may cause sillosis.

EFFECTS AND HAZARDS OF INGESTION (SWALLOWING):
None known.

Emergency and First Aid Procedures

TREATMENT FOR EYE CONTACT:

Flush eyes with plenty of water for at least 15 minutes. If irritation persists, see physician

TREATMENT FOR SKIN CONTACT:

Wash skin with soap and water.

TREATMENT FOR INHALATION (BREATHING);

Move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention.

TREATMENT FOR INGESTION (SWALLOWING): Drink plenty of water.

Precautions for Safe Handling and Use

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Use dust suppressant and sweep up spill. Avoid excessive dust.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, state, and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Handle with care, avoid dust. Store in a cool dry place.

OTHER PRECAUTIONS:

This product is for professional use only as stated in directions, by dentist or other person knowledgeable about this material.

Control Measures

RESPIRATORY PROTECTION:

NIOSH approved respirator for protection against silicosis producing dust.

	EXHAUST VENTILATION	
Use exh	aust fan.	
SPECIA	L VENTILATION:	
Exit area	· · · · · · · · · · · · · · · · · · ·	
МЕСНА	NICAL (GENERAL) VENTILATION:	
Dust col	lector	
OTHER	VENTILATION:	
Open wi	indows, if necessary	
PROTE	CTION GLOVES:	
For hygi-	enic purposes	
EYE PR	OTECTION:	
Safety g	lasses at minimum	
OTHER	PROTECTIVE EQUIPMENT:	
Uniform	or lab coat	
WORK.	AND HYGIENIC PRACTICES:	
Maintain	asepsis, wash hands after contact.	

Additional Information

This MSDS was prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29CFR 1910.1200) and is to be used only for this product. The information contained in this sheet is , to the best of our knowledge, believed to be accurate

Health Hazard Index:	Ratings:
SEVERE HAZARD	1
SERIOUS HAZARD	2
MODERATE HAZARD	3
SLIGHT HAZARD	4
MINIMUM HAZARD	(S)

Shipping Information

REGULATED IATA:

N/A

PROPER SHIPPING NAME:

Gypsum

HAZARD CLASS:

N/A

IDENTIFICATION NUMBER:

N/A

PACKAGING GROUP:

N/A

LABEL: N/A

To the best of our knowledge, the information contained herein is accurate. However, The Harry J. Bosworth company does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.