

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

**1** Identification

- · Product identifier
- Trade name: EXAFLEX PUTTY (Catalyst)

 Relevant identified uses of the substance or mixture and uses advised against Dental material

The product is intended for professional use.

To avoid risks for humans and environment obtain instructions.

- · Application of the substance / the mixture Dental impression material
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

GC America Inc. 3737 W. 127th Street Alsip, IL 60803 USA

sds@gcamerica.com

· Information department: Regulatory Affairs

Emergency telephone number:

During normal opening times (Mon.-Fri. 8:00 AM-5:00 PM CST): +1 (708) 597-0900 Transportation (CHEMTREC®) Emergency Telephone No. +1 (800) 424-9300

### 2 Hazard(s) identification

#### · Classification of the substance or mixture

Acute Tox. 4 H332 Harmful if inhaled.

STOT SE 3 H335 May cause respiratory irritation.

Eye Irrit. 2B H320 Causes eye irritation.

· Additional information:

The information provided is in regards to the toxicity and hazard rating(s) of the individual component(s) in the formulation. The associated risk(s) depends on the route(s) of exposure. The hazard rating system is based entirely on the existence of the risk(s) and does not take into account the likelihood of reduced risk(s) through proper usage and handling.

#### · Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



Signal word Warning
 Hazard statements
 Harmful if inhaled.
 Causes eye irritation.
 May cause respiratory irritation.

(Contd. on page 2)

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

## Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 1) Precautionary statements Avoid breathing dust/fume/gas/mist/vapors/spray If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: NFPA ratings (scale 0 - 4) Health = 1Fire = 0Reactivity = 1 · HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1 0 Fire = 0FIRE Reactivity = 1 **REACTIVITY** 1 Other hazards Results of PBT and vPvB assessment • **PBT:** Not applicable. · vPvB: Not applicable.

#### 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

#### Dangerous components:

112026 00 0	oilion diovido, omorphous	60-80%
112926-00-8	silicon dioxide, amorphous	00-00%
	catalyst**	5-10%

#### · Additional information:

If a substance is marked with \*\*, then substance is a trade secret. This is allowed under OSHA's Hazard Communication Standard (HCS) as a trade secret and under GHS as Confidential Business Information (CBI).

#### 4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product. If symptoms persist consult doctor.
- After inhalation: Supply fresh air or oxygen; call for doctor. In case of unconsciousness place patient stably in side position for transportation. Do not use mouth to mouth or mouth to nose resuscitation.
- After skin contact:
- Rinse with warm water.

If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

## Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 2)

After eye contact:
 Protect unharmed eye.
 Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- Information for doctor:
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### **5** Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.
- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### 6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Remove persons from danger area.
 Avoid formation of dust.
 Avoid contact with the eyes and skin.
 Wear protective clothing.
 Environmental precautions:

Do not allow product to reach sewage system or any water course. Do not allow to penetrate the ground/soil.

- Methods and material for containment and cleaning up:
   Pick up mechanically.
   Prevent formation of dust.
   Dispose of the collected material according to regulations.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- **Precautions for safe handling** Observe instructions for use.

(Contd. on page 4)

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

# Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 3)
re good ventilation/exhaustion at the workplace. ent formation of dust.
ot inhale dust / smoke / mist.
leposit of dust which cannot be avoided must be regularly removed.
I contact with the eyes and skin.
mation about protection against explosions and fires: can combine with air to form an explosive mixture.
age: irements to be met by storerooms and receptacles:
only in unopened original receptacles.
mation about storage in one common storage facility: Store away from foodstuffs.
ner information about storage conditions: Observe instructions for use / storage.
ific end use(s) No further relevant information available.
osure controls/personal protection
tional information about design of technical systems: No further data; see item 7.
rol parameters
ponents with limit values that require monitoring at the workplace:
26-00-8 silicon dioxide, amorphous
Long-term value: 2 mg/m <sup>3</sup> 20mppcf or 80mg/m3 /%SiO2; 1mppcf = 0.1 mg/m <sup>3</sup>
Long-term value: 6 mg/m <sup>3</sup>
See Pocket Guide App. C
TLV Withdrawn
yst**
Long-term value: 0.002 mg/m <sup>3</sup>
soluble salts, as Pt
Long-term value: 1* 0.002** mg/m <sup>3</sup>
*Metal **soluble salts, as Pt
Long-term value: 1* 0.002** mg/m <sup>3</sup> *metal **soluble salts, as Pt
tional information: The lists that were valid during the creation were used as basis.
-
sure controls onal protective equipment:
eral protective and hygienic measures:
usual precautionary measures for handling chemicals should be followed.
pt inhale dust / smoke / mist.
I contact with the eyes and skin.
n hands before breaks and at the end of work.
ediately remove all soiled and contaminated clothing.
thing equipment: Suitable respiratory protective device recommended. Action of hands: Protective gloves
rial of gloves
selection of the suitable gloves does not only depend on the material, but also on further marks of
ty and varies from manufacturer to manufacturer. As the product is a preparation of several
ances, the resistance of the glove material can not be calculated in advance and has therefore to
ecked prior to the application. (Contd. on page 5)

(Contd. of page 4)

# Safety Data Sheet acc. to OSHA HCS 29 CFR 1910.1200

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

Trade name: EXAFLEX PUTTY (Catalyst)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses

Information on basic physical and General Information	chemical properties	
Appearance:		
Form:	Pasty	
Color:	Blue	
Odor:	Odorless	
Odor threshold: pH-value:	Not determined.	
•	Not applicable.	
Change in condition	l ludoto maine d	
Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 160 °C (320 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not determined.	
Ignition temperature:	Undetermined.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not applicable.	
Density at 20 °C (68 °F):	1.67 g/cm³ (13.936 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not applicable.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with	Incolubio	
Water:	Insoluble.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Solvent content: Organic solvents:	0.0 %	
Solids content:	100.0 %	

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 5)

· Other information

No further relevant information available.

## 10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability Stable at ambient temperature.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### **11** Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: No further relevant information available.
- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

IARC (International Agency for Research on Cancer)	
silicon dioxide, amorphous	3
cobalt aluminate blue spinel	
NTP (National Toxicology Program)	
None of the ingredients is listed.	
OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
Carcinogenic categories' legend: IARC Group 1: The agent is carcinogenic to humans. IARC Group 2A: The agent is probably carcinogenic to humans. IARC Group 2B: The agent is possibly carcinogenic to humans. IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans. IARC Group 4: The agent is probably not carcinogenic to humans. NTP K: Known to be human carcinogen. NTP R: Reasonably anticipated to be human carcinogen.	

(Contd. on page 7)

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 6)

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

#### **13 Disposal considerations**

#### · Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

UN-Number DOT, ADR, ADN, IMDG, IATA	Void	
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA Class	Void	
Packing group DOT, ADR, IMDG, IATA	Void	
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	<b>II of</b> Not applicable.	

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 7)

· UN "Model Regulation":

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
   SARA (Superfund Amendments and Reauthorization Act)
- Section 355 (extremely hazardous substances):
- None of the ingredient is listed.
- Section 313 (Specific toxic chemical listings):
- None of the ingredients is listed.

#### • TSCA (Toxic Substances Control Act):

vinyl dimethylpolysiloxane

catalyst\*\*

#### · Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

#### • TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

#### · GHS label elements

- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



# Signal word Warning Hazard statements Harmful if inhaled. Causes eye irritation. May cause respiratory irritation. Precautionary statements Avoid breathing dust/fume/gas/mist/vapors/spray If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

USA

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

## Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 8)

Other information		
Department issuing MSI	<b>JS:</b> Regulatory Affairs	
Contact:		
Regulatory Affairs		
Telephone No. +1 (708) 5	97-0900	
sds@gcamerica.com		
Date of preparation / las	revision 02/24/2015 / -	
Abbreviations and acror		
	em of Classification and Labelling of Chemicals	
HCS: Hazard Communication St		
MSDS: Material Safety Data She	et	
SDS: Safety Data Sheet	u transport interpational des marghandises dengarquess per voies de pavigation intériours	
	u transport international des marchandises dangereuses par voies de navigation intérieure ng the International Carriage of Dangerous Goods by Inland Waterways)	
ECHA: European Chemicals Ag		
OSHA: Occupational Safety and	d Health Administration (USA)	
	transport des marchandises dangereuses par Route (European Agreement concerning th	
International Carriage of Danger IMDG: International Maritime Co		
DOT: US Department of Transpo		
IATA: International Air Transport		
	f Governmental Industrial Hygienists	
	e (division of the American Chemical Society)	
NFPA: National Fire Protection A HMIS: Hazardous Materials Ider		
LC50: Lethal concentration, 50 p		
LD50: Lethal dose, 50 percent		
PBT: Persistent, Bioaccumulativ		
vPvB: very Persistent and very E		
Acute Tox. 4: Acute toxicity, Haz Eve Irrit, 2B: Serious eve damac	e/eye irritation, Hazard Category 2B	
	n toxicity - Single exposure, Hazard Category 3	
Sources		
Manufacturers' MSDSs/S	3DSs	
	.gov/dts/chemicalsampling/toc/chmcas.html)	
<ul> <li>TOXNET (http://toxnet.nl</li> </ul>		
<ul> <li>ECHA (http://echa.europ</li> </ul>		
<ul> <li>EnviChem (www.echem)</li> </ul>		
Notes:		
	Registered Trademark of the American Chemical Society.	
	red service mark of the American Chemistry Council, Inc.	
-	previous version altered. This version replaces all previous versions.	
Disclaimer:	ad barain is ballound to be true and securate llowever, all statements	
	ed herein is believed to be true and accurate. However, all statements	
	estions are made without any guarantee, representation or warranty, expres	
	nerefore, no warranty is made or to be implied that the information set out in	
	or complete, and we accordingly exclude all liability in connection with the use	
	roducts referred to herein. All such risks are assumed by the purchaser/user	
	herein is also subject to change without notice. For the avoidance of doubt	
nowever, nothing in this d	ocument excludes or limits our liability for death or personal injury caused by	

our negligence or for fraudulent misrepresentation.