according to Regulation (EC) No 1907/2006

Luxatemp Ultra

Print date: 03.07.2014

Product code: 1300_GHS

Page 1 of 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Luxatemp Ultra

Product group:

Endprodukt

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH	
Street:	Elbgaustraße 248	
Place:	D-22547 Hamburg	
Telephone:	+49. (0) 40. 84006-0	Telefax: +49. (0) 40. 84006-222
e-mail:	info@dmg-dental.com	
Internet:	www.dmg-dental.com	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant R phrases: Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact.

GHS classification

Hazard Statements: May cause respiratory irritation. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction.

2.2. Label elements

Signal word:	Warning
Pictograms:	GHS07



Hazard statements

H335	May cause respiratory irritation.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Precautionary statements

P302+P352

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

according to Regulation (EC) No 1907/2006

Luxatemp Ultra Product code: 1300 GHS

Print date: 03.07.2014

Page 2 of 4

Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Consult physician.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons

High power water jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

Luxatemp Ultra			
rint date: 03.07.2014	Product code: 1300	_GHS	Page 3 of 4
Protective and hygiene measure	S		
When using do not early when the second seco	at or drink.		
Respiratory protection			
The following must be	e prevented: inhalation.		
Hand protection			
Tested protective glo	ves are to be worn: Suitable material	NBR (Nitrile rubber).	
Eye protection			
Tightly sealed safety	glasses.		
.1. Information on basic physical a Physical state:	Paste		
Colour:	characteristic		
Odour:	ester		
		Test metho	d
pH-Value (at 20 °C):		ca. 7	
Changes in the physical state			
Boiling point:		>250 °C	
point of decomposition:		200 °C	
Flash point:		>150 °C	
Ignition temperature:		>380 °C	

Ignition temperature:	>380 °C
Vapour pressure: (at 20 °C)	1 hPa
Density:	1,5 g/cm³
Water solubility:	10 g/L
Vapour density:	1

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

heat. Light.

Decomposition takes place from temperatures above: 200 $^\circ\text{C}$ Decomposition under formation of: Acrylate.

10.5. Incompatible materials

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

LD50: Rat. 5000 mg/kg

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation. Irritant effect on the eye:

Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

according to Regulation (EC) No 1907/2006

Luxatemp Ultra

Print date: 03.07.2014

Product code: 1300_GHS

Page 4 of 4

SECTION 12: Ecological information

12.1. Toxicity

Acute fish toxicity LC50: >360 mg/l/48h

12.2. Persistence and degradability

Preparation not tested.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge. Paste: Carry out a burning of harzardous waste according to official regulations.

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances Classified as hazardous waste.

SECTION 14: Transport information

Other applicable information

Not a hazardous material with respect to these transportation regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

- 36/37/38 Irritating to eyes, respiratory system and skin.
- 43 May cause sensitisation by skin contact.

Full text of H statements referred to under Sections 2 and 3

H317	May cause an allergic skin reaction.
11040	

- H319 Causes serious eye irritation.
 - H335 May cause respiratory irritation.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)