

NAME OF PRODUCT: TRIM® PLUS Liquid SDS DATE: 04/13/2015

FILE NO.: SDS936

### **SECTION 1: IDENTIFICATION**

PRODUCT NAME: TRIM PLUS Liquid

**PRODUCT CODES:** 0921930, 0921936, 0921937

IDENTIFIED USES: Dentistry
USES ADVISED AGAINST: Non-dental use

MANUFACTURER: Harry J. Bosworth Company

ADDRESS: 7227 North Hamlin Avenue, Skokie, Illinois 60076-3999, USA

 TELEPHONE:
 847-679-3400

 FAX:
 847-679-2080

 EMAIL:
 hjbinfo@bosworth.com

 EMERGENCY PHONE:
 800-535-5053 (US and Canada)

352-323-3500 (International)

### **SECTION 2: HAZARDS IDENTIFICATION**

**CLASSIFICATION:** Flammable liquids (Category 2)

Acute toxicity, Oral (Category 5)
Acute toxicity, Dermal (Category 5)
Skin irritation (Category 2)
Skin sensitization (Category 1)
Acute toxicity, Inhalation (Category 5)

Specific target organ toxicity - single exposure (Category 3), Respiratory system

Specific target organ toxicity - repeated exposure (Category 2)

Chronic aquatic toxicity (Category 4)

LABELING: FDA regulated device - exempt from Regulation (US) 29 CFR 1910.1200.

PICTOGRAM:

SIGNAL WORD: Danger

HAZARD STATEMENTS: H225 Highly flammable liquid and vapor.
H303 May be harmful if swallowed.
H312 May be harmful in sontest with skill.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H333 May be harmful if inhaled.
 H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

**PRECAUTIONARY STATEMENTS:** P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P234 Keep only in original container. P235+P410 Keep cool. Protect from sunlight.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse

skin with water/ shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

oreathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

PREPARED BY: SS PAGE 1 OF 5



NAME OF PRODUCT: TRIM® PLUS Liquid SDS DATE: 04/13/2015

P308+P313 IF exposed or concerned: Get medical advice/ attention.
P312 Call a POISON CENTER or doctor/ physician if you feel unwell.

P321 Specific treatment (see supplemental first aid instructions on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide

FILE NO.: SDS936

for extinction.

P391 Collect spillage.
P402 Store in a dry place.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container to an approved waste disposal plant.

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

COMPONENT	CAS NO.	%WT	OSHA PEL - TWA	ACGIH TLV - TWA	CLASSIFICATION
Methyl	80-62-6	60-100	100 ppm	50 ppm	Flam. Liq. 2; Skin Irrit. 2; Skin Sens. 1;
methacrylate					STOT SE 3; H225, H315, H317, H335
N,N-Dimethyl-	99-97-8	1-5	N/E	N/E	Flam. Liq. 4; Acute Tox. 3; STOT RE 2;
p-toluidine					Aquatic Acute 3; Aquatic Chronic 3;
					H227, H301+H311+H331, H373, H412

For full text of H-statements mentioned in this section, see section 16.

### **SECTION 4: FIRST-AID MEASURES**

**INHALATION:** Move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

**SKIN:** Wash off with soap and plenty of water. Consult a physician.

EYE: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water.

Consult a physician.

## **SECTION 5: FIRE-FIGHTING MEASURES**

SUITABLE EXTINGUISHING MEDIA: Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and nitrogen.

SPECIAL HAZARDS: Sealed containers exposed to elevated temperatures may rupture explosively due to polymerization. Vapors

are heavier than air and may travel to ignition source. Vapors are uninhibited and may form polymers in vents

or flame arrestors resulting in stoppage of vents.

ADVICE FOR FIREFIGHTERS: Fight fires from safe distance or protected areas. Cool containers of material exposed to heat with cold water

spray. Wear self contained breathing apparatus for firefighting if necessary.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

**PERSONAL PRECAUTIONS:** Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form

explosive concentrations. Vapors can accumulate in low areas.

ENVIRONMENTAL PRECAUTIONS: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the

environment must be avoided.

CONTAINMENT AND CLEANUP: Soak up with inert absorbent material and collect with an electrically protected vacuum cleaner or by wet-

brushing. Place in suitable, closed container for disposal according to official regulations.

# **SECTION 7: HANDLING AND STORAGE**

PRECAUTIONS FOR SAFE HANDLING: Product is intended for dental use only. Handling of this product should be by trained dental healthcare

professionals only. Observe normal care for working with chemicals. Avoid contact with the eyes and skin. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. Keep away from foodstuffs, beverages and animal feed.

CONDITIONS FOR SAFE STORAGE: Store only in the original package. Keep container tightly sealed in a dry and well-ventilated place. Protect

from heat and direct sunlight. Store away from food and beverages.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

PREPARED BY: SS PAGE 2 OF 5



NAME OF PRODUCT: TRIM® PLUS Liquid SDS DATE: 04/13/2015

ENGINEERING CONTROLS: Handle in accordance with good industrial hygiene and safety practice. Use with adequate general or local

exhaust ventilation to maintain exposure levels below the occupational exposure limits. Local exhaust ventilation is preferred since it prevents contamination dispersion into the work area by controlling it at its source. Provide eyewash and safety shower if contact or splash hazard exists. Wash hands before breaks and

FILE NO.: SDS936

at the end of work.

EYE/FACE PROTECTION: Safety glasses.

**SKIN PROTECTION:** Glove material impermeable and resistant to the product.

**BODY PROTECTION:** Protective work clothing.

**RESPIRATORY PROTECTION:** NIOSH (US) or CEN (EU) approved respirators and components.

ENVIRONMENTAL EXPOSURE: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the

environment must be avoided.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE/COLOR: Clear, colorless liquid

ODOR: Acrid

**BOILING POINT:** 216°F (102°C) **FLASH POINT:** 50°F (10°C)

 EVAPORATION RATE (BuAc = 1.0):
 3

 UPPER FLAMMABILITY LIMIT:
 12.5

 LOWER FLAMMABILITY LIMIT:
 2.1

 VAPOR PRESSURE:
 29 mmHg

 VAPOR DENSITY (AIR=1.0):
 3.5

 RELATIVE DENSITY (H2O=1.0):
 0.95 g/cm³

 WATER SOLUBILITY:
 1.5 wt%

### **SECTION 10: STABILITY AND REACTIVITY**

CHEMICAL STABILITY: Stable under recommended storage conditions. Polymerizes with evolution of heat. Avoid contact with

incompatible materials. Unless inhibited, product can polymerize, raising temperature and pressure, possibly rupturing container. Check inhibitor content often adding to bulk liquid if needed. Do not blanket or mix with

oxygen-free gas as it renders inhibitor ineffective.

HAZARDOUS REACTIONS: Vapors may form explosive mixture with air. Polymerizes readily unless inhibited.

**CONDITIONS TO AVOID:** Heat, flames, sparks, aging, contamination and absence of an oxygen containing atmosphere above the

product. May polymerize upon exposure to light. Extremes of temperature and direct sunlight.

INCOMPATIBLE MATERIALS: Oxidizing agents, peroxides, amines, bases, acids, reducing agents, halogens. Material has strong solvent

properties and can soften paint and rubber.

 $\textbf{HAZARDOUS DECOMPOSITION PRODUCTS:} \ \ \textbf{Oxides of carbon and nitrogen}.$ 

### **SECTION 11: TOXICOLOGICAL INFORMATION**

POTENTIAL HEALTH EFFECTS: EYES: May cause eye irritation with redness, tearing and stinging.

**<u>SKIN:</u>** May cause skin irritation with redness, swelling and itching. Repeated or prolonged contact may cause

drying, defatting of the skin and dermatitis.

<u>INGESTION:</u> May cause mucous membrane and gastrointestinal irritation with nausea, vomiting and diarrhea. May cause nervous system depression with symptoms of headache, dizziness, nausea, vomiting, weakness,

fatigue, confusion, and unconsciousness.

<u>INHALATION:</u> May cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness, drowsiness, nausea, vomiting, and unconsciousness. High vapor concentrations may cause burning sensation of the nose and throat and watering of the eyes.

**SKIN SENSITIZATION:** May cause allergic skin reaction.

**CARCINOGENICITY:** OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or possible carcinogen by OSHA.

 $\underline{\textbf{ACGIH:}} \ \textbf{No component of this product present at levels greater than or equal to 0.1\% is identified as a level of the product present at level of the presen$ 

carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or

anticipated carcinogen by NTP.

IARC: Methyl methacrylate is identified as not classifiable as to its carcinogenicity to humans by IARC.

## **SECTION 12: ECOLOGICAL INFORMATION**

PREPARED BY: SS PAGE 3 OF 5



NAME OF PRODUCT: TRIM® PLUS Liquid

ADVERSE EFFECTS: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. May cause

long lasting harmful effects to aquatic life. Avoid release to the environment.

**SECTION 13: DISPOSAL CONSIDERATIONS** 

**PRODUCT:** Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical

incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Disposal must be made

FILE NO.: SDS936

**SDS DATE:** 04/13/2015

according to official regulations.

**CONTAMINATED PACKAGING:** Dispose of as unused product.

**SECTION 14: TRANSPORT INFORMATION** 

UN NUMBER: UN1247

PROPER SHIPPING NAME: Methyl methacrylate monomer, stabilized

HAZARD CLASS: 3
PACKING GROUP: ||

LABEL STATEMENT: Flammable Liquid

**SECTION 15: REGULATORY INFORMATION** 

**US FEDERAL REGULATIONS** 

**TSCA:** This product is an FDA regulated device and not subject to TSCA regulations.

CERCLA: This product is an FDA regulated device and not subject to reporting requirements. There may be specific

reporting requirements at the local, regional, or state level.

SARA 313 TOXIC CHEMICALS: The following components are subject to reporting levels established by SARA Title III, Section 313 (40 CFR

372): Methyl Methacrylate, CAS NO. 80-62-6.

SARA 311/312 HAZARDS: This product is an FDA regulated device and not subject to reporting requirements.

**US STATE REGULATIONS** 

CALIFORNIA PROPOSITION 65: This product may contain a chemical known to the State of California to cause cancer and/or reproductive

toxicity.

**INTERNATIONAL REGULATIONS** 

**CANADIAN ENVIRONMENTAL** 

PROTECTION ACT: This product is a medical device and not subject to chemical notification requirements.

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES

(EINECS): This product is a medical device and not subject to chemical notification requirements.

**SECTION 16: OTHER INFORMATION** 

**FULL TEXT OF H STATEMENTS REFERRED TO UNDER SECTION 3** 

Acute Tox. Acute toxicity
Aquatic Acute Acute Acute aquatic toxicity
Aquatic Chronic Chronic aquatic toxicity
Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapor.

H227 Combustible liquid.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Skin Irrit. Skin irritation

PREPARED BY: SS PAGE 4 OF 5



NAME OF PRODUCT: TRIM® PLUS Liquid

Skin Sens. Skin sensitization

STOT RE Specific target organ toxicity – repeated exposure STOT SE Specific target organ toxicity – single exposure

### NFPA RATING

Health Hazard 2
Fire Hazard 3
Reactivity Hazard 2

**PREPARATION INFORMATION:** This SDS was prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200) and is to be used only for this product.

**DISCLAIMER:** To the best of our knowledge, the information contained herein is accurate. However, The Harry J. Bosworth Company does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

FILE NO.: SDS936

**SDS DATE:** 04/13/2015

PREPARED BY: SS PAGE 5 OF 5