May be used to comply with Administration DSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements. EDENTITY (As Used on Label and List)	Occupational Safety and Health		
29 CFR 1910.1200. Standard must be consulted for specific requirements.			
consulted for specific requirements.	(Non-Mandatory Form)		
	Form Approved		
	OMB No. 1218-0072 NOTE: Blank spaces are not permitted. If any item is		
Temrex Diamond Polishing Paste	not applicable, or no information is available, the space must be marked to indicate that.		
Section I			
Manufacturer's Name	Emergency Telephone Number		
Temrex Corporation	(800) 645-1226		
Address (Number, Street, City, State, and ZIP Code) 112 Albany Avenue	Telephone Number for Information (516) 868-6221		
	Date Prepared		
P.O. Box 182	January 24, 2011		
Freeport, NY 11520	Signature of Preparer (optional)		
Section II – Hazardous Ingredients/Identity Information	Other Limits		
Hazardous Components (Specific Chemical Identity: Comi Recommended %(optional)	mon Name(s)) OSHA PEL ACGIH TLV		
Non-Ha	zardous		
Section III – Physical/Chemical Characteristics			
Boiling Point	Specific Gravity (H2O = 1)		
Boiling Point N/A	ca 1.2		
N/A Vapor Pressure (mm Hg.)	ca 1.2 Melting Point		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A	ca 1.2 Melting Point 50°C		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A	ca 1.2 Melting Point		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A	ca 1.2 Melting Point 50°C		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A Solubility in Water	ca 1.2 Melting Point 50°C Evaporation Rate (Butyl Acetate = 1)		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A Solubility in Water Partia	ca 1.2 Melting Point 50°C		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A Solubility in Water Partia Appearance and Odor	ca 1.2 Melting Point 50°C Evaporation Rate (Butyl Acetate = 1)		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A Solubility in Water Partia Appearance and Odor Grayish p	ca 1.2 Melting Point 50°C Evaporation Rate (Butyl Acetate = 1) Illy soluble.		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A Solubility in Water Partia Appearance and Odor Grayish p Section IV – Fire and Explosion Hazard Data	ca 1.2 Melting Point 50°C Evaporation Rate (Butyl Acetate = 1) Illy soluble. paste; no odor.		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A Solubility in Water Partia Appearance and Odor Grayish p Section IV – Fire and Explosion Hazard Data Flash Point (Method Used) Flammable Li	ca 1.2 Melting Point 50°C Evaporation Rate (Butyl Acetate = 1) Illy soluble. paste; no odor.		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A Solubility in Water Partia Appearance and Odor Grayish p Section IV – Fire and Explosion Hazard Data Flash Point (Method Used) N/A Extinguishing Media	ca 1.2 Melting Point 50°C Evaporation Rate (Butyl Acetate = 1) Illy soluble. Daste; no odor. Imits LEL		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A Solubility in Water Partia Appearance and Odor Section IV – Fire and Explosion Hazard Data Flash Point (Method Used) N/A Extinguishing Media	ca 1.2 Melting Point 50°C Evaporation Rate (Butyl Acetate = 1) Illy soluble. asste; no odor. UEL UEL I/A N/A		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A Solubility in Water Partia Appearance and Odor Grayish p Section IV – Fire and Explosion Hazard Data Flash Point (Method Used) N/A NExtinguishing Media Special Fire Fighting Procedures	ca 1.2 Melting Point 50°C Evaporation Rate (Butyl Acetate = 1) Illy soluble. asste; no odor. UEL UEL I/A N/A		
Boiling Point N/A Vapor Pressure (mm Hg.) N/A Vapor Density (AIR = 1) N/A Solubility in Water Partia Appearance and Odor Grayish p Section IV – Fire and Explosion Hazard Data Flash Point (Method Used) N/A NExtinguishing Media Special Fire Fighting Procedures	ca 1.2 Melting Point 50°C Evaporation Rate (Butyl Acetate = 1) Illy soluble. Paste; no odor. Imits LEL VA VA VA VA VA VA VA		

Section V – Reactiv	vity Data				
Stability	Unstable		Conditions to Avoid		
	Stable	x			
ncompatibility (M	aterials to Avoid)		None known.		
lazardous Decom	position or Byproduct	S			
			None		
Hazardous Polymerization	May Occur		Conditions to Avoid		
	Will Not Occur	x			
ection VI – Health	n Hazard Data				
oute(s) of Entry:	li	nhalati	on?	Skin?	Ingestion?
lealth Hazards (Ad	cute and Chronic)		None known.		
			None known.		
Carcinogenicity:	genicity: NTP? IARC Monographs?		aphs?	OSHA Regulated?	
	N/A		N/A	N/A	
igns and Symptor	ns of Exposure		None known.		
Aedical Condition	s Generally Aggravate				
		N	ot anticipated.		
Emergency and Fir	st Aid Procedures				
	utions for Safe Handl	ing an			
	in Case Material is Re				
steps to be Taken			vith water.		
Naste Disposal M		our Di	sposal OK		
Precautions to Be	Taken in Handling an	d Stori	ng		
Other Precautions		ons; avo	oid exposure to open fla	ame.	
Section VIII – Cont	rol Measures	a la			
Respiratory Prote	ction (Specify Type)		None required.		
Venthilation	Local Exhaust			Special	
	Mechanical (Gene	eral)		Other	
Protective Gloves				Eye Protection Not required.	
Other Protective (Not require Clothing or Equipment	t			required.
Work/Hygienic Pr	actices		No specific requirement	5.	
Nony Hybienie FI			Routine.		
			Page 2		

529/45775

* U.S.G.P.O.: 1966 - 491 -